

Approved for Zone 0. The redesigned Survivor features a low-profile bezel that doesn't interfere with gear and equipment. We also redesigned the clip and added a reinforced D-ring so your light hangs forward consistently.



Custom designed optic with optional, interchangeable Smoke Cutter® plugs for preferred beam pattern:

- Black plug significantly reduces peripheral light for a tighter beam
- Amber plug reduces peripheral light and eye fatigue caused by glare



Strong spring-loaded clip securely grabs onto belts and gear; D-ring features forward hanging orientation

Rubber dome push-button switch easy to use with gloves

Low-profile design doesn't interfere with gear and equipment

New optic combines low-profile with strong performance and a narrow beam with optimum peripheral illumination

Rugged nylon polymer body is virtually indestructible

Multiple power sources:
Rechargeable lithium ion battery;
 also accepts 4 "AA" alkaline or
 4 "AA" lithium batteries

No tools needed to change batteries



C4® LED with high, low, emergency flash and moonlight modes

- High for a super-bright beam that pierces through smoke: 41,000 candela; 175 lumens; 405m beam distance; runs 3.5 hours (lithium rech); runs 8 hours (AA alkaline or AA lithium)
- Low for bright light and longer run time: 14,000 candela; 60 lumens; 237m beam distance; runs 10 hours (lithium rech); runs 20 hours (AA alkaline or AA lithium)
- Flash for signaling: runs 5 hours
- Moonlight mode provides low-level lighting for battery conservation: runs 15 days

Optimized electronics provide regulated intensity

Custom optic for narrow beam and optimum peripheral illumination

FTZU 15 ATEX 0046X; IEC Ex FTZU 15.0029X

II 1G Ex ia IIB T3/T4 Ga; II 2G Ex ia IIC T3/T4 Gb

IP66 rated design; dust tight and water resistant; 2 meter impact resistance tested

17.92 cm; 388g (with lithium rechargeable or AA alkaline); 354g (with AA lithium)

Limited Lifetime Warranty

Visit www.streamlight.com for full warranty information

See reverse for item numbers